

# COACH LANTERN

IP44

## A traditional and elegant lantern design

The Coach lantern is manufactured in vandal resistant polycarbonate with all the anti weathering benefits over die cast aluminium.

The wall mounted units benefit from the versatile QUICK FIT system, the unique fast fit electrical connection eases installation and helps prevent the end user installing the product incorrectly.



- Easy to install.
- IP44.
- PIR: Day time walk test.
- Shatter-proof Polycarbonate detector.
- PIR Range of 6 Metres.
- 110° Angle of detection.
- Designed to BS EN 60598.

### Material

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black.
- Diffuser: Vandal resistant polycarbonate.

### Installation

- Quick Fit connection.

### Standards


- IP44.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.




# COACH LANTERN



Other options or configurations may be available, please contact us on 01709 374898 or email [sales@asdlighting.com](mailto:sales@asdlighting.com) for advice.



| Size |       |
|------|-------|
| A    | 273mm |
| B    | 417mm |



## Material

- Body: Vandal resistant polycarbonate self-extinguishing fire properties in black.
- Diffuser: Vandal resistant polycarbonate.

## Installation

- Quick Fit connection.

## Standards

- IP44.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.